

750 Watt C-Band Rack Mount High Power Amplifier



FEATURES

- *Touch screen interface*
- *Compact 4RU chassis*
- *Built-in redundancy controller*
- *Extended frequency bands available*
- *Ethernet interface, remote diagnostics*
- *Parameter trend analysis*

The **XTRT-750C** is a highly efficient rack mountable traveling wave tube amplifier (TWTA) designed for fixed and mobile uplink applications. The unit includes RF gain control, a solid state pre-amplifier, RF filters, cooling, and monitoring and control (M&C) systems. Rack space is conserved because the amplifier occupies only 4 rack units (7 inches) of a standard 19 inch rack cabinet. Nominal weight is 75 pounds.

The **XTRT-750C** is a 750W C-band amplifier with a touch screen front panel for easy customer interface. The display shows HPA status, parameter trend analysis and event logs, and remote diagnostics can be easily performed via the Ethernet interface. Also, because the display can show and control waveguide switches or a combiner, the need for separate external controllers is eliminated for common architectures.

The **XTRT-750C** incorporates high efficiency, dual stage collector TWTs. Reliability is enhanced because both prime power consumption and internal operating temperatures are reduced for both the linear and saturated modes of operation. Depending upon user requirements these amplifiers can be configured for either single thread or redundant system operation.

PERFORMANCE SPECIFICATION

Parameters	XTRT-750C
FREQUENCY RANGE (extended frequency coverage available)	5.850 to 6.425 GHz (5.850 to 6.650 GHz)
OUTPUT POWER	
Traveling Wave Tube	750 W
Rated Power @ Amplifier Flange (minimum)	650 W
GAIN	
Large Signal (minimum)	70 dB
Small Signal (minimum)	75 dB
Attenuator Range (continuous)	25 dB
Maximum SSG Variation Over:	
Any Narrow Band	1.0 dB per 40 MHz
Full Band	2.5 dB/575 MHz
Slope (maximum)	± 0.04 dB/MHz
Stability, 24 hr. (maximum)	± 0.25 dB
Stability, Temperature (maximum)	± 1.0 dB over temperature range at any frequency
INTERMODULATION (maximum) with two equal carriers	-18 dBc @ 4 dB total output power backoff (-26 dBc with linearizer option)
HARMONIC OUTPUT (maximum)	-60 dBc
AM/PM CONVERSION (maximum)	2.5°/dB at 6 dB below rated power (2°/dB @ 3 dB below rated power with optional linearizer)
NOISE POWER (maximum)	
Transmit Band	-70 dBW/4kHz
Receive Band	-150 dBW/4 kHz 3.7 to 4.2 GHz
GROUP DELAY (maximum)	
Bandwidth	Any 40 MHz
Linear	0.01 nS/MHz
Parabolic	0.005 nS/MH ²
Ripple	0.5 nS/Pk-Pk
RESIDUAL AM NOISE (maximum)	-50 dBc to 10 kHz -20 (1.5 + logf) dBc to 500 kHz -85 dBc above 500 kHz
PHASE NOISE (maximum)	12 dB below IESS phase noise profile AC fundamental -50 dBc Sum of all spurs -47 dBc
VSWR	
Input (maximum)	1.3:1
Output (maximum)	1.3:1