

400 Watt Ku-Band High Efficiency Antenna Mount High Power Amplifier with Block Upconverter



FEATURES

- 13.75 to 14.5 GHz
- High efficiency: draws 850W @ linear output
- Light weight, compact package: 31 lbs.
- Includes L-band BUC

The **XTD-400KHE-B1** series is a compact, antenna mountable, traveling wave tube amplifier designed for low cost installation and long life. Intended for outdoor operation, the self contained **XTD-400KHE-B1** is designed for transportable applications where high efficiency, light weight, and high ambient temperature operation are required.

RF filters, cooling, and monitor & control (M&C) systems are all self contained within the package. A high frequency resonant conversion power supply is used that accepts a wide range of prime power (100 to 240 VAC). A remote external controller is available to operate the HPA from a user selected location. Depending upon user requirements, these high power amplifiers can be configured for single thread, redundant, or phase combined configurations.



PERFORMANCE SPECIFICATION

Parameters	XTD-400KHE-B1
FREQUENCY RANGE (extended frequency coverage available)	
Output	13.75 to 14.5 GHz
Input	950 to 1700 MHz
LO Frequency	12800 MHz
Input Level, w/o damage (maximum)	10 dBm
Reference Signal Frequency	external 10 MHz
10 MHz Power Level	2 dBm \pm 5 dB
OUTPUT POWER	
Traveling Wave Tube	400 Watts
Maximum Transmit Power	200 Watts
Linear Power @ Amplifier Flange (minimum)	170 Watts with optional linearizer 90 Watts without linearizer
GAIN	
Large Signal (minimum)	67 dB
Small Signal (minimum)	67 dB
Attenuator Range (continuous)	30 dB, 0.1 dB steps
Maximum SSG Variation Over	
Any Narrow Band	1.0 dB per 80 MHz
Full Band	\pm 2 dB
Slope (maximum)	\pm 0.04 dB/MHz
Stability, 24 hr. (maximum)	\pm 0.25 dB
Stability, Temperature (maximum)	\pm 1.0 dB over temperature range at any frequency
INTERMODULATION (maximum) relative to the sum of two equal carriers	-26 dBc @ P_{LINEAR} with optional linearizer
SPECTRAL REGROWTH @ 1 SR offset	-30 dBc @ P_{LINEAR}
AM/PM CONVERSION (maximum)	2.0 deg/dB @ P_{LINEAR}
HARMONIC OUTPUT (maximum)	-60 dBc
NOISE POWER (maximum)	
Transmit Band	-70 dBW/4 kHz
Receive Band	-150 dBW/4 kHz 10.95 to 12.75 GHz
GROUP DELAY (maximum)	
Bandwidth	Any 80 MHz
Linear	0.01 nS/MHz
Parabolic	0.005 nS/MHz ²
Ripple	0.5 nS/Pk-Pk
RESIDUAL AM NOISE (maximum)	-60 dBc > 100 kHz from carrier AC fundamental -50 dBc Sum of all spurs -47 dBc
PHASE NOISE (maximum)	5 dB below IESS phase noise profile
VSWR	
Input (maximum)	1.6:1
Output (maximum)	1.3:1